



 pezzolato

Drum Chipper **PTH 40.70 MULTICUT** Serie

*Wood chipper with multi-knivessystem drum
and big feeding hopper*

GREENLINE

PTH 40.70 MULTICUT



PTH 40.70 MULTICUT

The chipper PTH 40.70 MULTICUT is part of the well-established range of chippers by Pezzolato. A chipper equipped with a closed drum at four or eight knives. The machine presents an extremely robust frame, typical quality of all Pezzolato's chippers, and guarantees reliability and excellent performance. The huge charging opening, which can be closed for the best

compactness of the machine during transport, allows the smooth introduction of voluminous material even by mechanical means (inlet passage is 640*400 mm). For the manual feeding, the chipper is equipped with a robust safety bar, for the safer usage of the machine by the operator.

A big horizontal roller with spikes, together with



Space saving during transportation



Big feeding hopper



a conveyor positioned inside the hopper, allows the easy introduction of the material to be processed. The interchangeable calibrating grid allows to choose the dimension of the chips and guarantees homogeneous and uniform chips. The discharge fan with its large diameter allows the expulsion of the chips without obstacles through the discharge pipe, equipped with an

adjustable deflector at its end. It can be driven by the tractor's PTO or by an autonomous diesel or electric motor. The main wear parts are especially studied to be easily changed at reasonable costs.



Multi-knives system drum



These chippers guarantees the production of calibrated chips

EXTRAS AND CONFIGURATIONS

- \ **NO STRESS electronic device**, available on all standard machines, automatically regulates the in-feed of material according to the available power

- \ **Sieving grids**, for chip calibration with different sizes, easy to replace

- \ **Radio or cable remote control**, to manage the chippers main activities at a distance

- \ **Removable security bar**, for hand or crane feeding

- \ **Hydraulic orientation** (deflector rotation and direction) **discharge tube**

- \ **Low- or high-speed towing trailer**, with air or hydraulic brakes

- \ **Forestry cranes, with or without cabin**, in customized configuration

- \ **Stationary version with electric motor**

- \ **Feeding chain along the entire hopper** to make easier the feeding with bulky material

- \ **"M version" machine**, driven by Diesel engine



Driven by diesel engine



Low speed towing trailer



Feeding chain without hooks and security bar for hand or crane feeding



Stationary version with electric motor

TECHNICAL DATA		PTH 40.70 MULTICUT
Minimum tractor power:	Hp	70
Maximum tractor power:	Hp	130
Diesel engine power:	Hp	174 - 238
Electric engine power:	kW	55 - 75
Maximum inlet passage:	mm	640 x 400
Knives:	n°	4
Maximum chipping diameter (soft wood)*:	mm	400
Maximum chipping diameter (hard wood)*:	mm	300
Drum width:	mm	640
Drum diameter:	mm	520
Upper roller width:	mm	640
Hourly troughthput*:	m ³ /h	20 - 25

* Diameters and production declared are variable according to the available power, wood type and chip size.

